

Universal wall sleeve

for any type of wall

UFR200/300 B

Article no.: 3030466854, GTIN: 4052487243179



- **Printed scale for adjusting to specific wall thickness**
- **Flange connection for the processing of plastic-modified bitumen thick coatings**
- **Tried and tested solution for use in fresh concrete composite systems**

Enables sealing in all types of wall when combined with sealing flange and 3-bridge seals. Can be cut to length on site to specific wall thickness using printed scale.



Picture may differ from selected product

FACTS

Advantages:

- Lightweight
- Simple installation in the formwork
- Can be cut to length on site
- Can be used in all types of wall including element constructions

Scope of delivery:

- 2 pieces closing covers



Properties:

- FHRK-certified
- Break-resistant, inherently stable
- Sealed ready for installation

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Pipe: PVC-U
- Integrated patch flange: ABS
- 3-ribbed seals: EPDM
- Closing cover: PE

Tightness:

- gastight and watertight

FEATURES

| | |
|-----------------|-----|
| D1 (mm): | 200 |
| D2 (mm): | 214 |
| D4 (mm): | 311 |
| D3 (mm): | 336 |
| Lenght (mm): | 300 |

PICTURES

