

# Standard press seal

with powder coating

## HSD400 GC 1x273 b40 A2/EPDM55

Article no.: 1610700273, GTIN: 4052487042574



- **optical and tangible installation security due to integrated control opening**

- **Optimum corrosion protection when used in conjunction with components**

For sealing new pipes to be installed or pipes that have already been laid in galvanised wall sleeves. Available for delivery for all standard pipe sizes.



Picture may differ from selected product

## FACTS

### Advantages:

- Can be split on site up to  $\varnothing$  200 mm for retrofit installation
- Split as standard at and above  $\varnothing$  250 mm
- Available from stock

### Dimensions:

- Sealing width: 40 mm

### Properties:

- FHRK-certified
- U-profile: maximum stability for press segments



## Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates: stainless steel V2A (AISI 304L), also powder coated
- Screws and nuts: stainless steel, V2A (AISI 304L)
- Rubber: EPDM

## Tightness:

- gastight and watertight
- radon tight

## FEATURES

|                                   |         |
|-----------------------------------|---------|
| Wall sleeve ID (mm):              | 400     |
| Suitable for medium pipe OD (mm): | 273-276 |

## PICTURES

