

# Plastic spiral conduit hose for cable entry system

# Hateflex14090/2000B

Article no.: 3030366927, GTIN: 4052487233156

- Flexible plastic spiral hose (peak compressive strength 745 N).
  - A pressure-tight cable entry system (for up to 2.5 bar external pressure) can be created using the associated connection components.

Flexible and very rugged plastic spiral hose. A pressure-tight cable entry system can be created with the associated connection components.



Picture may differ from selected product

## **FACTS**

#### **Advantages:**

- Empty conduit route without sleeve available up to 25 m
- Empty conduit system that can be built over
- Smooth inner surface for gentle cable pulling

## Scope of delivery:

• Coils in lengths of 25 m (special lengths are available in 0.5 m sections)

#### **Dimensions:**

- ID: 91 mm ± 1 mm
- OD: 104 mm ± 1 mm

#### **Properties:**

- Peak compressive strength: 745 N
- Installation temperature: +5°C to +50°C
- Weatherproof and will not rot
- Resistant to brine and seawater
- Installation temperature from +5° to +50°C
- Weather-proof, UV-resistant and rot-resistant
- Resistant to brine and seawater

#### **Material:**

Hard PVC/soft PVC

### **Tightness:**

• gastight and watertight to 2.5 bar

# **FEATURES**

Length (m): 2.0

# **PICTURES**





Tel. +49 7322 1333-0

Fax +49 7322 1333-999