

Always. Reliable. Tight.

Slanted single wall insert

for setting in concrete

HSI90 1xz K S_°/X

Picture may differ from selected product

- **3-ribbed seal is sprayed on to create pressure-tight seal with concrete**

For slanted cable entries from any direction and an optimum bending radius when feeding in and sealing cables or when connecting cable ducts.

FACTS

Application range:

- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Item is delivered ready to install for installation flush with formwork
- System seal can be connected on one side (e.g. cable duct connection and cable seal)
- Packages created ex works (single row)
- Cable entry in a single angle 30°/45° or 60°

Scope of delivery:

- Polystyrene wedge
- Attachment frame
- Pressure-tight closing cover

Dimensions:

- Centre distance: 135 mm

Properties:

- Attention! The special solution used for the inclined building entry may mean that the specified minimum wall thickness for waterproof concrete walls is undershot.
- The use of a double slanted wall insert (determined by the thickness of the wall) is always recommended

Material:

- Wall insert: ABS with TPE 3-ribbed seal
- Adapter pipe: PVC
- Closing cover: ABS with EPDM seal
- Attachment frame: steel St37
- Polystyrene wedge

Tightness:

- Gastight and watertight to 2.0 bar