

Standard press seal

with super segmented ring technology and polymer press plates

HRK150 SSG 6x10-36 b40 PAGF/A4/EPDM55

Article no.: 3030300048, GTIN: 4052487126373



- **Integrated segmented ring technology for individual adjustment to cable diameters on site**
- **Press plates have form-fit connections**

For sealing a water line or a power cable and communications lines in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



Picture may differ from selected product

FACTS

Advantages:

- Available from stock

Scope of delivery:

- Blind plug (if there is more than one cable entry)
- 1 piece Knife
- 1 piece Lubricating stick

Dimensions:

- Sealing width: 40 mm



Properties:

- FHRK-certified

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Press plates: glass fibre reinforced polyamide
- Rubber: EPDM
- Screws and nuts: rust-free stainless steel V4A (AISI 316L)

Tightness:

- gastight and watertight
- radon tight

FEATURES

Wall sleeve/core drilled hole ID (mm):	150
Openings:	6
Carrier pipe \varnothing_a (mm):	10-36
Packing unit:	1

PICTURES

