Universal wall sleeve

for any type of wall

UFR300/600

Article no.: 2800030600, GTIN: 4052487154130

- **Flange connection for the processing of plastic-modified bitumen thick coatings**
- **Tried and tested solution for use in fresh concrete composite systems**

Enables sealing in all types of wall when combined with sealing flange and 3-bridge seals.

Picture may differ from selected product

FACTS

Advantages:

- Lightweight
- Simple installation in the formwork
- Can be cut to length on site
- Can be used in all types of wall including element constructions

Scope of delivery:

- 2 pieces closing covers

Properties:

- FHRK-certified
- Break-resistant, inherently stable
- Sealed ready for installation

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Pipe: PVC-U
- Integrated patch flange: ABS
- 3-ribbed seals: EPDM
- Closing cover: PE

Tightness:

- gastight and watertight

FEATURES

D1 (mm):	300
D2 (mm):	316
D4 (mm):	436
D3 (mm):	472
Lenght (mm):	600
Packing unit:	1

PICTURES



Hauff-Technik GmbH & Co. KG
Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de