

Stainless steel flange

for retrofit dowelling

FA1x150/80/0 A2

Article no.: 910850000, GTIN: 4052487021043

For dowelling through existing recesses/break-throughs in walls or floor slabs.



Picture may differ from selected product

FACTS

Advantages:

- Tailor-made designs can also be produced
- Also available with multiple entries and in a variety of diameters

Scope of delivery:

- 1 piece Stainless steel flange
- 1 piece surface seal
- Fastenings

Dimensions:

- Standard flange dimensions OD or \square a equivalent to the corresponding wall sleeve ID + approx. 150 mm (for one entry, see the brochure for detailed information)
- Standard upper length: 80 mm

Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Flange: stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Surface seal: EPDM
- Fastenings: stainless steel V4A (AISI 316L)

FEATURES

| | |
|------------------------------------|-----|
| Wall sleeve ID (mm): | 150 |
| Wall sleeve wall thickness (mm) S: | 2 |
| Flange standard dimensions (mm): | 225 |

PICTURES



ACCESSORIES REQUIRED



EGO sealant