

# Fixed/loose flange wall sleeve made from stainless steel

for setting in concrete for black tank according to DIN 18533

FLFE1x100/0/240 DIN18533 A2

Article no.: 2500100240

For setting in concrete or mortar in walls, ceilings or floors.



Picture may differ from selected product

## FACTS

### Advantages:

- Tailor-made designs can also be produced
- Also available with multiple entries and in a variety of diameters
- Installation flush with formwork

### Scope of delivery:

- 1 piece Fixed/loose flange wall sleeve
- Bolts and nuts M20 (DIN 18533)
- With closing covers on both sides

## Dimensions:

- Standard fixed flange Øa equal to the relevant wall sleeve Øi + approx. 330 mm (for one passage)

## Application range:

- DIN 18533 W2.1-E, DIN 18533 W2.2-E

## Material:

- Fixed/loose flange wall sleeve: stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Closing cover: PE

## Tightness:

- gastight and watertight

## FEATURES

|                                    |     |
|------------------------------------|-----|
| Wall sleeve ID (mm) D1:            | 100 |
| Fixed flange OD (mm) D2:           | 425 |
| Loose flange OD (mm) D3:           | 415 |
| Wall sleeve wall thickness (mm) S: | 2   |
| wall thickness (mm):               | 240 |

## PICTURES



## ACCESSORIES REQUIRED



Rubber inlays