

# Seal insert for basic insert

## arranged side by side

### MSH Basic MBK R4

Article no.: 1551008100, GTIN: 4052487141345



- **All-around smooth surface for optimum connection of the finished flooring**

Gastight and watertight building entry for buildings without a basement for the collective feeding in of supply lines for gas, water, power and telecommunications. The building entry is installed in the MSH Basic - FUBO - E - SR 4 wall sleeve.



Picture may differ from selected product

## FACTS

### Advantages:

- Seals all supply lines through one entry
- All services are fed in and sealed separately
- The arrangement of the individual services is flexible

### Scope of delivery:

- 1 piece seal insert
- 2 pieces nail screws for attaching the seal insert
- 8 pieces self-tapping screws M8x45 for sealing service lines



## Dimensions:

- Width: 500 mm
- Length: 135 mm
- Height: 283 mm

## Properties:

- DVGW-certified
- Also required: closed sealing elements

## Material:

- Anchor plate: glass fibre reinforced polyamide
- Pipes: ABS with TPE
- Screws: stainless steel V2A (AISI 304L)

## Tightness:

- gastight and watertight to 1.0 bar

## Tests/Standards:

- DVGW VP 601

# FEATURES

Item: Dichteinsatz für Rohbauteil